VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

AirFiber Dish 26dBi, 3 GHz, Slant 45

Artikelnummer: AF-3G26-S45







€317,00

Incl. 21% BTW

Pair an airFiber X antenna with an airFiber X radio to create the endpoint of a high-performance, Point-to-Point (PtP) bridge or network backhaul (air…

Pair an airFiber X antenna with an airFiber X radio to create the endpoint of a high-performance, Point-to-Point (PtP) bridge or network backhaul (airFiber X radio sold separately).

Specifications AF-3G26-S45

Dimensions: 650 x 300 mm (25.59 x 11.81")

Weight: 9.8 kg (21.61 lb)

Frequency Range: 3.3 - 3.8 GHz

Gain: 26 dBi

+ 45 degrees Beamwidth: 7 degrees (3 dB)

- 45 degrees Beamwidth: 7 degrees (3 dB)

F/B Ratio: 33 dB

Max. VSWR: 1.4:1

Wind Loading: 787 N @ 200 km/h (177 lbf @125 mph)

Wind Survivability: 200 km/h (125 mph)

Polariation: Dual-Linear

Cross-pol Isolation: 35 dB Min.

ETSI Specification: EN 302 326 DN2

Mounting: Universal Pole Mount, airFiber X Radio Bracket, and Weatherproof RF Connectors Included

Package Contents

Dish Reflector, Antenna Feed, Mounting Bracket, Protective Shroud, Pole Clamps, Stabilizer Brackets (2), RF Cables (2), Elevation Rod Assembly, M10x150 Carriage Bolts (4), M10x100 Carriage Bolts (2), M10x25 Carriage Bolts (3), M4 Bolts (4), Quick Start Guide.

*

Indien dit product boven de toegestane limieten gebruikt wordt, is dit niet langer vergunningsvrij en zelfs illegaal (max zendvermogen: 100 mW op 2,4GHz en 200 mW op 5GHz). Wij raden u aan de standaard configuratie v.w.b. de landeninstelling en/of vermogensinstelling van de apparatuur niet te wijzigen. Het gebruik van meer dan het wettelijke toegestane vermogen kan leiden tot verminderde bruikbaarheid van WIFI in uw onmiddellijke omgeving.