

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

Bullet AC Titanium - BulletAC-IP67

Artikelnummer: BulletAC-IP67

**€147,00**

Incl. 21% BTW

Let op, de BulletAC-IP67 is een airMAX AC apparaat en kan alleen met andere airMAX AC apparaten communiceren. Het is dus geen WiFi apparaat.
The Bull...

Let op, de BulletAC-IP67 is een airMAX AC apparaat en kan alleen met andere airMAX AC apparaten communiceren. Het is dus geen WiFi apparaat.

The Bullet AC is a fully integrated radio that delivers up to 300+ Mbps Real TCP/IP throughput.

Dual-Band Frequency

The Bullet AC covers both 2.4 and 5 GHz radio bands, covering a wide range of frequencies that work well for both short and long-distance links.

Output Power

The B-DB-AC offers up to 22 dBm of output power, while the BulletAC IP67 offers 21 dBm.

Passive Power over Ethernet (PoE)

24V Passive PoE functionality is included. Both power and data are carried over a single Ethernet cable to the Bullet AC. Use a PoE Adapter (not included) or an optional PoE switch.

Weatherproof Design

The durable casing of the Bullet AC can withstand nature's harshest outdoor elements. The BulletAC-IP67 features a robust IP67 weather-resistant body that protects against dust and water.

Plug and Play Integration

No special tools or antennas are required to install the Bullet AC. Simply plug in and go.

Specifications BulletAC-IP67

Dimensions: 190 x 46 x 46 mm (7.48 x 1.81 x 1.81)

Weight: 213 g (7.51 oz)

Enclosure: Aluminum and Rubber

Networking Interface: Gigabit Ethernet Port

Antenna Connector: N-Type Connector

Throughput:

- 2.4 GHz: 160+ Mbps

- 5 GHz: 300+ Mbps

Max. Power Consumption: 7W

Output Power: 21 dBm

Power Supply: AC to 24VDC, 0.3A Gigabit PoE Adapter

Power Method: 24V Passive PoE (Pairs 4, 5+; 7, 8 Return)

ESD/EMP Protection: +/- 24 kV Contact / Air

Operating Temperature: -40 to 70 C (-40 to 158 F)

Operating Humidity: 5 to 95% Condensing

Shock and Vibration: ETSI300-019-1.4

Certifications: CE, FCC, IC

Package Contents

Bullet, N-male - N-female 90 coupler