VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

EdgePower 54Volt 150W

Artikelnummer: EP-54V-150W







€230,00

Incl. 21% BTW

The EdgePower is a high-power, modular PSU system designed to connect to EdgePoint routers/switches, and provide reliable power to attached PoE device…

The EdgePower is a high-power, modular PSU system designed to connect to EdgePoint routers/switches, and provide reliable power to attached PoE devices. The EdgePower uses modular SUs for flexible configuration options. The EdgePower can utilize two modular PSUs to provide up to 300W of power, or be configured to provide up to 150W of power with an automatic PSU backup. The EdgePower consists of a rack-mountable, two-bay housing and control unit, and includes one AC-DC 54V, 150W PSU module. The second PSU bay can house an AC-DC or DC-DC PSU module (sold separately).

High Power

The EdgePower provides up to 150W of power output. With an optional PSU in the secondary bay, the EdgePower may be configured to deliver up to 300W of power.

Backup PSU

The secondary PSU may be configured as a backup PSU. In backup mode, the secondary PSU remains inactive and offline. If failure of the primary PSU is detected, the secondary PSU automatically activates to supply continuous power.

Web UI

Designed for convenient management, the EdgePower Configuration Interface allows administrators to configure and monitor PSU features in a simple, graphical user interface.
The EdgePower may be connected to the LAN for remote monitoring and configuration.

Specifications EdgePower, 54v, 150W

Dimensions: 299.8 x 286.9 x 42.55 mm (11.89 x 11.3 x 1.675")

Weight without Mount Brackets: 2.7 kg (5.95 lb)

Interfaces:

- Networking: (1) 10/100 Mbps RJ45 Port

- Management: Ethernet In-Band, Web UI

Maximum Power Output: 150W (1 PSU Module),300W (2 PSU Modules: 150W Each)

Power Method: 100-240VAC/50-60 Hz, Universal Input

Power Supply Module: 54V, 150W AC/DC, Model EP-54V-150W-AC, Installed in PSU 1

LEDs:

- Power: System On/Of

- Ethernet: Management Port Link

- PSU: PSU1+PSU2, PSU1/PSU2

Rack-Mount: Yes, 1U High

ESD/EMP Protection: Air +/- 24kV; Contact +/- 24kV

Operating Temperature: 0 to 40 C (32 to 104 F)

Operating Humidity: 10 - 90% Noncondensing

Certifications: CE, FCC, IC

Package Contents

EdgePower, Power Cord, Mount Brackets (4), Bracket Screws (16), Rack-Mount Screws (4), Cage Nuts (4), Mounting Screws (8), Screw Anchors (8), Quick Start Guide.

TERMS OF USE:

All Ethernet cabling runs must use CAT5 (or above). It is the customer's responsibility to follow local country regulations, including operation within legal frequency

channels, output power, indoor cabling requirements, and Dynamic Frequency Selection (DFS) requirements.