VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

LiteAP GPS

Artikelnummer: LAP-GPS







€123,00

Incl. 21% BTW

Featuring an ultra-lightweight form factor, the LiteAP GPS was designed to be an affordable cost/performance solution for long-distance, wireless broa…

Featuring an ultra-lightweight form factor, the LiteAP GPS was designed to be an affordable cost/performance solution for long-distance, wireless broadband bridging. Each of these models operates in the worldwide, license-free 5 GHz frequency range with high-performance speeds. The LiteAP GPS combines proprietary hardware and software technologies to deliver its breakthrough combination of throughput and range

with cost-effective value.

Specifications LiteAP GPS

Dimensions: 360.98 x 124.57 x 71.28 mm

Weight: (No Mount): 752 g (1.66 lb)

Mounting Kit: Pole Mounting Kit (Included)

Networking Interface: (1) 10/100/1000 Ethernet Port

Memory: DDR2 64 MB

Max. Power Consumption: 7.1W

Max. TX Power: 25 dBm

Antenna Gain: 17 dBi

Power Supply: 24V, 0.3A PoE Adapter (Included)

Power Method: Passive PoE (Pairs 4, 5+; 7, 8 Return)

Processor Specs: Atheros MIPS 74Kc, 533 MHz

Shock and Vibration: ETSI300-019-1.4

ETSI Specification: EN 302 326 DN2

ESD/EMP Protection: +/- 24 kV Contact / Air

RoHS Compliance: Yes

Operating Temperature: -40 to 70 C (-40 to 158 F)

Operating Humidity: 5 to 95% Noncondensing

Certifications: FCC, IC, CE

Package Contents

LiteAP GPS, Ball Joint Mount, Metal Strap, Gigabit PoE (24v, 0.3A) with Mounting Bracket, Power Cord.

*

Indien dit product boven de toegestane limieten gebruikt wordt, is dit niet langer vergunningsvrij en zelfs illegaal (max zendvermogen: 100 mW op 2,4GHz en 200 mW op 5GHz). Wij raden u aan de standaard configuratie v.w.b. de landeninstelling en/of vermogensinstelling van de apparatuur niet te wijzigen. Het gebruik van meer dan het wettelijke toegestane vermogen kan leiden tot verminderde bruikbaarheid van WIFI in uw onmiddellijke omgeving.