VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

LiteBeam 5AC Gen 2 - 23 dBi

Artikelnummer: LBE-5AC-Gen2





€84,00

Incl. 21% BTW

Ubiquiti Networks launches the latest generation of airMAX CPE (Customer Premises Equipment), the LiteBeam 5AC Gen 2, with dedicated Wi-Fi managem…

Ubiquiti Networks launches the

latest generation of airMAX CPE

(Customer Premises Equipment), the

LiteBeam 5AC Gen 2, with dedicated

Wi-Fi management.

Improved Noise Immunity

The LiteBeam 5AC Gen 2 directs

RF energy in a tighter beamwidth.

With the focus in one direction, the LiteBeam 5AC Gen 2 blocks or spatially filters out noise, so noise immunity is improved. This feature is especially important in an area crowded with other RF signals of the same or similar frequency.

Integrated Design

Ubiquitis InnerFeed technology integrates the radio into the feedhorn of an antenna, so there is no need for a cable. This improves performance because it eliminates cable losses. Featuring high performance and innovative mechanical design, the LiteBeam 5AC Gen 2 is versatile and cost-effective to deploy.

Management Wi-Fi Radio

The LiteBeam AC integrates a separate Wi-Fi radio for fast and easy setup using your mobile device. (Android/iOS).

Specifications LBE-5AC-GEN2

LAN speed:(1) 10/100/1000Mbps

Gigabit LAN: Yes

RAM memory size [MB]: 64

CPU: MIPS 74Kc

CPU frequency [MHz]: 650

Purpose: Outdoor

Buttons: Reset

Operating temperature [C: -40 up to 70

Dimensions [mm]: 272x358x272

Max. power consumption [W]: 7

Power over Ethernet: 24V DC

PoE type: Input

Transmission speed - WiFi 5GHz [Mb/s]: 866

Antenna gain [dBi]: 23

Package Contents

Antenna Feed Center Reflector, Panel, Side Reflector Panels (2), Feed Receiver, Azimuth Mount, Elevation Mount, Metal Strap, Knob Kit, Gigabit PoE (24V, 0.3A) with Mounting Bracket, Power Cord, Quick Start Guide