

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

NanoSwitch - Outdoor 4 port 24V PoE Switch

Artikelnummer: N-SW



€46,00

Incl. 21% BTW

Introducing the Ubiquiti Networks NanoSwitch, an unmanaged switch with four Gigabit Ethernet ports. For its total non-blocking line rate, the NanoSwitch...

Introducing the Ubiquiti Networks NanoSwitch, an unmanaged switch with four Gigabit Ethernet ports. For its total non-blocking line rate, the NanoSwitch supports up to 4 Gbps.

(1) Gigabit 24V Passive PoE In Port

(3) Gigabit 24V Passive PoE Out Ports

Featuring a durable, weatherproof form factor, the NanoSwitch is ideal for outdoor deployment. For quick installation, the compact NanoSwitch can be easily mounted on a pole or wall.

Specifications

Dimensions: 196.4 x 93.5 x 32.4 mm (7.73 x 3.68 x 1.28")

Enclosure Characteristics: White Polycarbonate

Total Non-Blocking Line Rate: 4 Gbps

Typical Power Consumption: 1.5W

Passive PoE Max. Wattage per Port: 24V, 2-Pair, 1A per Port (24W)

Total Passive PoE Max. Wattage: 24V, 2-Pair, 1A for 3 Ports (24W)

Power Method: Passive 24V, 2-Pair PoE In

Power Supply: POE-24-24W PoE Adapter (Not Included)

Passive PoE Voltage Range: 21.6 - 26.4V

LEDs: Speed/Link/Activity (All Ports)

Networking Interfaces: (4) 10/100/1000 Mbps RJ45 Ports|

ESD/EMP Protection: Air: +/- 24 kV, Contact: +/- 24 kV

Operating Temperature: -30 to 70 C (-22 to 158 F)

Operating Humidity: 5 to 95% Noncondensing

Shock and Vibration: ETSI300-019-1.4 Standard

Certifications: CE, FCC, IC

Package Contents

NanoSwitch, Self-Tapping Screw, Metal Straps (2), Quick Start Guide