

**VDB Computers B.V.**

Vlakdissel 9  
1648 HJ De Goorn  
info@vdbcomputers.nl  
0229-544704

**Tweede kans/Refurbished - UniFi Switch XG - 6 poort, 210W PoE budget**

Artikelnummer: OOB-US-XG-6POE

**€639,00**

Incl. 21% BTW

**Retour gekomen met geopende verpakking, maar verder in nieuwstaat heeft VDB Computers B.V. enkele producten in de uitverkoop. De producten zijn verpak...**

Retour gekomen met geopende verpakking, maar verder in nieuwstaat heeft VDB Computers B.V. enkele producten in de uitverkoop. De producten zijn verpakt in de originele doos en bevatten nauwelijks gebruikerssporen. Alleen de doos is eenmalig open geweest.

Build and expand your network with the Ubiquiti UniFi Switch XG 6POE, model US-XG-6POE. It is a fully managed, 6-port, 10G switch with 802.3bt PoE++. For deployment versatility, four 10G RJ45 ports offer 802.3bt PoE++ for powering devices, and two SFP+ ports are designed for high-capacity fiber uplinks. The UniFi Switch XG 6POE offers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss.

(4) 100/1000 Mbps and 2.5/5/10G RJ45 Ports

(2) 1/10 Gbps SFP+ Ports

(4) 802.bt PoE++ Ports

Non-Blocking Throughput: 60 Gbps

Switching Capacity: 120 Gbps

Forwarding Rate: 89.3 Mpps

Maximum Power Consumption: 40W

External 210W AC/DC Adapter (Included)

DC Input Option (Redundant or Stand-Alone)

Specifications UniFi Switch XG 6POE

Dimensions: 165 x 268.1 x 31.8 mm (6.50 x 10.56 x 1.25")

Weight: 1.3 kg (2.87 lb)

Interfaces Networking: (4) 100/1000 Mbps and 2.5/5/10G RJ45 Ports, (2) 1/10G SFP+ Ethernet Ports

Interfaces Management: Ethernet In-Band, (1) RJ45 Serial Port Out-of-Band, (1) USB Type C Port Out-of-Band

Power Method: 54VDC, 3.88A Power Adapter (Included) or DC Input with Terminal Block

Power Supply: External AC/DC Adapter (Included) or DC Power Source

Supported Voltage Range: 44 to 57VDC

Max. Power Consumption (Excluding PoE Output): 40W

LEDs:

- System: Status

- RJ45 Data Ports: PoE; Speed/Link/Activity

- SFP+ Data Ports: Link/Activity

Shock and Vibration: ETSI300-019-1.4 Standard

Operating Temperature: -5 to 45 C (23 to 113 F)

Operating Humidity: 5 to 95% Noncondensing

Certifications: CE, FCC, IC

Package Contents

UniFi Switch XG 6POE, Mount Brackets (2), Bracket Screws (8), Mounting Screws (4), Screw Anchors (4), Power Adapter, Power Cord, Cable Clip.