VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

UF-Instant

Artikelnummer: UF-Instant









€48,00

Incl. 21% BTW

Certifications	CE, FCC, IC
Dimensions	69.46 x 13.70 x 11.30 mm
Management Interface	In-Band Ethernet PON
Max. Power Consumption	2W
Memory Information	32 MB DDR
Networking Interface Speeds GPON WAN, ITU G.984 GbE LAN	2.488 Gbps Downstream 1.244 Gbps Upstream 1 Gbps
Networking Interfaces	(1) SC/APC, GPON WAN (1) SGMII Ethernet LAN
Normal Optical Power Range	TX (Class B+): 1.5 to 5 dBm RX: -28 to -8 dBm
Operating Humidity	10 to 90%
Operating Temperature	-10 to 45 C
Power Method	SFP
Power Supply	3.3V
Processor Specs	MIPS 100 MHz
Supported Voltage Range	3.3V
Weight	30 g

Point-to-multipoint access module with a SFP port and powerful Layer 2/3 switching capability.

Gigabit Passive Optical Network CPE.

Feature:
…

Point-to-multipoint access module with a SFP port and powerful Layer 2/3 switching capability.

Gigabit Passive Optical Network CPE.

Feature:

High-Performance GPON CPE

Up to 2.4 Gbps Downstream and 1.2 Gbps Upstream GPON structure

Supports up to 20 km GPON Links

Powerful Layer 2/3 Management Features

(1) GPON WAN Port, SC/APC

(1) 1Gbps SFP interface

Specifications

Dimensions 69.46 x 13.70 x 11.30 mm

Weight 30 g

Networking Interfaces (1) SC/APC, GPON WAN

(1) SGMII Ethernet LAN

Networking Interface

Speeds

GPON WAN, ITU G.984

GbE LAN

2.488 Gbps Downstream

1.244 Gbps Upstream

1 Gbps

Management Interface In-Band Ethernet

PON

Normal Optical

Power Range TX (Class B+): 1.5 to 5 dBm

RX: -28 to -8 dBm

Power Method SFP

Power Supply 3.3V

Max. Power Consumption 2W

Supported Voltage Range 3.3V

Processor Specs MIPS 100 MHz

Memory Information 32 MB DDR

Operating Temperature -10 to 45 C

Operating Humidity 10 to 90%

Certifications CE, FCC, IC

Package Contents:

UFiber Instant.