

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

UFiber Nano G Network Unit UF-NANO

Artikelnummer: UF-NANO



€90,00

Incl. 21% BTW

The UFiber Nano G is a robust, high-performance GPON CPE that features an informational LED display and a sleek, sophisticated industrial design.

...

The UFiber Nano G is a robust, high-performance GPON CPE that features an informational LED display and a sleek, sophisticated industrial design.

(1) GPON WAN Port and (1) Gigabit LAN Ethernet Port

Digital Display LED for Status Reporting

7W Max. Power Consumption

Specifications UF-Nano

Dimensions: 77 x 77 x 28 mm (3.03 x 3.03 x 1.1")

Weight: 110 g (3.88 oz)

Networking Interfaces: (1) SC/APC, GPON WAN, (1) Gigabit RJ45, Ethernet LAN

Networking Interface Speeds:

- (1) GPON WAN, ITU G.984: 2.488 Gbps Downstream, 1.244 Gbps Upstream

- (1) GbE LAN: 10/100/1000 Mbps

Management Interface: In-Band Ethernet/PON

Normal Optical Power Range: TX (Class B+): 1.5 to 5 dBm, RX: -28 to -8 dBm

Power Method: Passive PoE (Pins +4, 5; -7, 8) Dying Gasp Support

Power Supply: PoE Adapter: 24V, 0.3A (Included)

Max. Power Consumption: 7W

Supported Voltage Range: 20V to 28V

Processor Specs : MIPS32, 240 MHz

Memory Information: 128 MB DDR3

Buttons: (1) Display Information (1) Reset

Operating Temperature: -10 to 45 C (14 to 113 F)

Operating Humidity: 5 to 95% Noncondensing

Certifications: CE, FCC, IC

Package Contents

Nano G, Wall Mount Bracket, Screws (4), Sxrew Anchors (4), Gigabit PoE (24V, 0.3A) with Mount Bracket, Power Cord.