AFGEDRUKT OP
21-11-2026

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

UFiber WiFi

Artikelnummer: UF-WiFi







€89,00

Incl. 21% BTW

UFiber WIFI is a robust, high-performance GPON CPE that offers routing, four LAN ports, and Wi-Fi. It is powered by 24V passive PoE or a 24V, 0.5A pow…

UFiber WIFI is a robust, high-performance GPON CPE that offers routing, four LAN ports, and Wi-Fi. It is powered by 24V passive PoE or a 24V, 0.5A power adapter.

High-Performance GPON CPE

GPON WAN Port SC/APC Fiber Connector

4-Port RJ45 10/100/1000 VLAN-aware Switch

802.11n WiFi

LED diodes for easy diagnostics

Up to 2.4 Gbps Downstream and 1.2 Gbps Upstream

Specifications UF-WiFi

Dimensions: 126.34 x 126.09 x 31.65 mm (4.97 x 4.96 x 1.25")

Weight: 190 g (6.70 oz)

Networking Interfaces:

- (1) SC/APC, GPON WAN

- (4) Gigabit RJ45, Ethernet LAN

- (1) Wi-Fi, 802.11n

Networking Interface Speeds:

GPON WAN, ITU G.984: 2.488 Gbps Downstream, 1.244 Gbps Upstream

GbE LAN: 10/100/1000 Mbps:

Wi-Fi: 300 Mbps:

Management Interface: In-Band Ethernet/PON

Normal Optical Power Range: TX (Class B+): 1.5 to 5 dBm, RX: -28 to -8 dBm

Power Method: DC Jack, 24VDC, 24V Passive PoE (Pins 4, 5+; 7, 8-)

Power Supply: 100-240VAC / 50-60 Hz Universal AC/DC, Power Adapter: 24V / 0.5A

Max. Power Consumption: 7W

Supported Voltage Range: 20 to 28V

Processor Specs: MIPS, 900 MHz

Memory Information: 256 MB DDR

Buttons: (1) Reset

Operating Temperature: -10 to 45 C (14 to 113 F)

Operating Humidity: 10 to 90% Noncondensing

Certifications: CE, FCC, IC

Package Contents

UFiber UF-WIFI, Screws (4), Screw Anchors (4), Power Adapter (24V, 0,5A).