AFGEDRUKT OP
21-11-2026

VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

UISP Cable Carrier - 305m outdoor CAT5e FTP kabel

Artikelnummer: UISP-Cable-Carrier







€240,00

Incl. 21% BTW

Anti-Crosstalk Divider	LDPE: 4.2*0.3 mm
Box Dimensions	330 x 425 x 340 mm
Box Weight	16 kg
Cable Color	Black
Cable Lenght	305m
Cable Shield (Aluminum Foil)	Thick: 0.060 mm, Extent: 20 mm
Cable Type	CAT5e, Shielded
Conductor	Solid Bare Copper
Conductor Diameter	0.500 +/- 0.005 mm
Conductor Wire Gauge	24 AWG
ESD Drain Wire	0.4 TC
Ethernet Support	Up to 1 Gbps
Installation Temperature	-20 to 60 C
Insulation Diameter	1.16 +/- 0.02 mm
Insulation Thickness	Avg. 0.295 mm Min. 0.29 mm
Insulation Type	Solid Polyethylene
Jacket Color	Black

Jacket Material	Polyethylene
Jacket Outer Diameter	6.8 +/- 0.30 mm
Jacket Thickness	Avg. 0.52 mm Min. 0.46 mm
Operation Temperature	-40 to 80 C
Rip Cord	Yes
Secondary Cable Shield (Braid)	16*8*0.16AA Density: 95%
Separation (Polyester Wrapping)	Thick: 0.025 mm, Extent: 20 mm
Standards	ANSI/TIA-568-C.2 (2009) ISO/IEC 11801 (Edition 2.2)
Storage Temperature	-30 to 75 C

Dit product heeft een naamswijziging gehad en was voorheen de TOUGHCable CARRIER (TC-CARRIER).

Ethernet kabel van industriele kwaliteit die uw n…

Dit product heeft een naamswijziging gehad en was voorheen de TOUGHCable CARRIER (TC-CARRIER).

Ethernet kabel van industriele kwaliteit die uw netwerk beschermt tegen elementaire en elektrostatische schade

De UISP-kabeldrager is een categorie 5e-kabel die meerlaagse elementaire bescherming biedt met een primaire gevlochten afscherming en een weerbestendige mantel die schade door regen, sneeuw en andere barre klimaat omstandigheden voorkomt.

De kabel is ook uitgerust met een afvoerdraad en interne folieafscherming om hem te beschermen tegen elektrostatische ontlading (ESD), en de anti-overspraakverdeler behoudt de signaalintegriteit, waardoor de kabel de Gigabit Ethernet-verbindingssnelheden kan behouden, zelfs wanneer er elektromagnetische interferentie aanwezig is.

1,000 ft (305 m) Category 5e cable

24 AWG massief koperen geleiderparen

Geisoleerde weerbestendige kabelmantel

Interne vlecht- en folieafscherming

Afvoerdraad die beschermt tegen elektrostatische ontlading schade

Anti overspraak verdeler

Mechanical

Box Dimensions 330 x 425 x 340 mm

Box Weight 16 kg

Cable Lenght 305m

Cable Color Black

Cable Type CAT5e, Shielded

Ethernet Support Up to 1 Gbps

Conductor Wire Gauge 24 AWG

Conductor Solid Bare Copper

Conductor Diameter 0.500 +/- 0.005 mm

Insulation Type Solid Polyethylene

Insulation Thickness Avg. 0.295 mm

Min. 0.29 mm

Insulation Diameter 1.16 +/- 0.02 mm

Separation (Polyester Wrapping) Thick: 0.025 mm,

Extent: 20 mm

Anti-Crosstalk Divider LDPE: 4.2*0.3 mm

Cable Shield (Aluminum Foil) Thick: 0.060 mm, Extent: 20 mm

ESD Drain Wire 0.4 TC

Rip Cord Yes

Secondary Cable Shield (Braid) 16*8*0.16AA Density: 95%

Jacket Material Polyethylene

Jacket Thickness Avg. 0.52 mm

Min. 0.46 mm

Jacket Outer Diameter 6.8 +/- 0.30 mm

Jacket Color Black

Storage Temperature -30 to 75 C

Installation Temperature -20 to 60 C

Operation Temperature -40 to 80 C

Standards ANSI/TIA-568-C.2 (2009)

ISO/IEC 11801 (Edition 2.2)

Package Contents

UISP Cable Carrier