VdB computers

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

UISP Cable Pro (TC-PRO) - 305m outdoor FTP kabel

Artikelnummer: UISP-Cable-Pro







€175,00

Incl. 21% BTW

Anti-Crosstalk Divider	None
Box Dimensions	330 x 330 x 340 mm
Box Weight	12 kg
Cable Color	Black
Cable Length	305 m
Cable Shield (Aluminum Foil)	Thick: 0.060 mm, Extent: 18 mm
Cable Type	CAT5e, Shielded
Conductor	Solid Bare Copper
Conductor Diameter	0.500 +/- 0.005 mm
Conductor Wire Gauge	24 AWG
ESD Drain Wire	0.4 CCS
Ethernet Support	Up to 1 Gbps
Installation Temperature	-20 to 60 C
Insulation Diameter	1.04 +/- 0.03 mm
Insulation Thickness	Avg. 0.26 mm, Min. 0.25 mm
Insulation Type	Solid Polyethylene
Jacket Color	Black

Jacket Material	Polyethylene
Jacket Outer Diameter	6.0 +/- 0.30 mm
Jacket Thickness	Avg. 0.50 mm, Min. 0.46 mm
Operation Temperature	-40 to 80 C
Rip Cord	Yes
Separation (Polyester Wrapping)	Thick: 0.025 mm, Extent: 20 mm
Standards	ANSI/TIA-568-C.2 (2009) ISO/IEC 11801 (Edition 2.2)
Storage Temperature	-30 to 75 C

Dit product heeft een naamswijziging gehad en was voorheen de TOUGHCable PRO (TC-PRO).

The UISP-Cable-Pro is een Cat 5e kabel met een sterk isolere…

Dit product heeft een naamswijziging gehad en was voorheen de TOUGHCable PRO (TC-PRO).

The UISP-Cable-Pro is een Cat 5e kabel met een sterk isolerende, weerbestendige mantel die schade door regen, sneeuw en andere extreme klimaat omstandigheden voorkomt. De kabel is ook versterkt met een interne folieafscherming en een afvoerdraad die hem gezamenlijk afschermt tegen elektrostatische ontlading (ESD) en hem in staat stelt om de Gigabit Ethernet-verbindingssnelheden te behouden, zelfs wanneer er elektromagnetische interferentie aanwezig is.

Feature:

1,000 ft (305 m) Category 5e cable

24 AWG massief koperen geleiderparen

Geisoleerde, weerbestendige kabelmantel

Mechanical

Box Dimensions 330 x 330 x 340 mm

Box Weight 12 kg

Cable Length 305 m

Cable Color Black

Cable Type CAT5e, Shielded

Ethernet Support Up to 1 Gbps

Conductor Wire Gauge 24 AWG

Conductor Solid Bare Copper

Conductor Diameter 0.500 +/- 0.005 mm

Insulation Type Solid Polyethylene

Insulation Thickness Avg. 0.26 mm, Min. 0.25 mm

Insulation Diameter 1.04 +/- 0.03 mm

Separation (Polyester Wrapping) Thick: 0.025 mm,

Extent: 20 mm

Anti-Crosstalk Divider None

Cable Shield (Aluminum Foil) Thick: 0.060 mm,

Extent: 18 mm

ESD Drain Wire 0.4 CCS

Rip Cord Yes

Jacket Material Polyethylene

Jacket Thickness Avg. 0.50 mm, Min. 0.46 mm

Jacket Outer Diameter 6.0 +/- 0.30 mm

Jacket Color Black

Storage Temperature -30 to 75 C

Installation Temperature -20 to 60 C

Operation Temperature -40 to 80 C

Standards ANSI/TIA-568-C.2 (2009)

ISO/IEC 11801 (Edition 2.2)

Package Contents

UISP Cable Pro