VDB Computers B.V.
Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

UniFi Cloud Key G2

Artikelnummer: UCK-G2









€153,00

Incl. 21% BTW

Buttons	(1) Power; (1) Reset
Certifications	CE, FCC, IC
Configuration Interface	BlueTooth LE with Ubiquiti Mobile Applications, Web browser
Dimensions	27.10 x 46.80 x 119.75 mm
Enclosure	Anodized Aluminum
LEDs	(1) Power, White/Blue
Management Interface	UniFi App; UniFi Network Interface
Max. Power Consumption	5W (PoE/Adapter)
Networking Interface	(1) 10/100/1000 Ethernet Port
Operating Humidity	20 to 80% Noncondensing
Operating Temperature	0 to 35 C (32 to 104 F)
Power Method	Standard 802.3 af PoE, DC 5V 1A Powered
Processor	APQ8053 with 2 GB RAM
Supported Voltage Range	Standard 802.3 af PoE, DC 5V 1A
Weight	150 g
EMMC Memory	32 GB

The Cloud Key Gen2 (UCK G2) is a next-generation UniFi OS Console that quadruples the power of its predecessor. Manage your UniFi system with the UCK …

The Cloud Key Gen2 (UCK G2) is a next-generation UniFi OS Console that quadruples the power of its predecessor.

Manage your UniFi system with the UCK G2. This slim but powerful UniFi OS Console can be set up and configured in minutes with UniFi's Bluetooth-powered mobile apps.

Review real-time network and device insights concisely presented on the console's front panel display and safeguard your entire UniFi system from sudden power loss with its built-in battery.

4X more powerful than the original Cloud Key

Easy Bluetooth setup with UniFi mobile app

Powered by 802.3af PoE or USB-C

Built-in battery for automatic safe shutdown

Front panel display for at-a-glance network details

LET OP:

Deze Cloud Key Gen2 wordt zonder microSD geleverd!

Specifications

Dimensions: 27.10 x 46.80 x 119.75 mm

Weight: 150 g

Enclosure: Anodized Aluminum

Processor: APQ8053 with 2 GB RAM

eMMC Memory: 32 GB

Management Interface: UniFi App; UniFi Network Interface

Networking Interface: (1) 10/100/1000 Ethernet Port

Configuration Interface: BlueTooth LE with Ubiquiti Mobile Applications, Web browser

Buttons: (1) Power; (1) Reset

LEDs: (1) Power, White/Blue

Power Method: Standard 802.3 af PoE, DC 5V 1A Powered

Supported Voltage Range: Standard 802.3 af PoE, DC 5V 1A

Max. Power Consumption: 5W (PoE/Adapter)

Operating Temperature: 0 to 35 C (32 to 104 F)

Operating Humidity: 20 to 80% Noncondensing

Certifications: CE, FCC, IC

Package contents

UCK-G2