VdB computers

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

AFGEDRUKT OP
21-11-2026

UniFi Gateway Pro

Artikelnummer: UXG-Pro







€624,00

Incl. 21% BTW

AC outlet/ RPS	Blue
Button	Factory reset
Certifications	CE, FCC, IC
Dimensions	442.4 x 43.7 x 285.6 mm
ESD/EMP protection	Air: +/- 15 kV, contact: +/- 8 kV
Enclosure materials	Front panel: aluminum CNC Top cover/base: SGCC steel
Ethernet	Green/amber
LCM display	(1) 1.3" touchscreen, Bootup animation: bootup in progress, Firmware upgrade icon: firmware upgrading
Management interface	Ethernet
Max. power consumption	30W
Memory information	2 GB DDR4
Networking interface LAN: WAN	(1) 1 GbE RJ45 port (1) 10G SFP+ port (1) 1 GbE RJ45 port (1) 10G SFP+ port
Operating humidity	5 - 95% noncondensing
Operating temperature	-10 to 40 C
Power method	(1) Universal AC input, 200-240VAC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5VDC, 2.87A

Power supply	AC/DC, internal, 50W
Processor	Quad-core ARM Cortex-A57 at 1.7 GHz
SFP+	White/green
Weight	3.42 kg

Dual-WAN security gateway ontworpen om middelgrote tot grote netwerken te beschermen met firewallconfiguratie en bedreigingsbeheerfuncties van bedrijf…

Dual-WAN security gateway ontworpen om middelgrote tot grote netwerken te beschermen met firewallconfiguratie en bedreigingsbeheerfuncties van bedrijfsklasse.

De UniFi Next-generation Gateway Pro (UXG Pro) is een krachtige security gateway die een veelzijdige netwerkinterface en enterprise-class bedreigingsbeheerfunctionaliteit levert voor middelgrote tot grote netwerken.

De UXG Pro is uitgerust met (2) WAN-poorten (GbE RJ45 en 10G SFP+) die failover-ondersteuning bieden, evenals (2) LAN-poorten (GbE RJ45 en 10G SFP+) voor de snelle connectiviteit die nodig is om de meest bandbreedte-intensieve toepassingen te ondersteunen. Het product blinkt ook uit als een complete netwerkbeveiligingsoplossing, met een volledige reeks functies voor het beperken van bedreigingen, waaronder diepe pakketinspectie (DPI), inbraakdetectie- en preventiesystemen (IDS/IPS) en gelaagde firewallconfiguratie.

De UXG Pro kan worden gekoppeld aan een Cloud Key Gen2 Plus om een zeer krachtige en veilige implementatie te creeren die volledig kan worden beheerd met de UniFi Network application (web/mobile).

1.7 GHz quad-core processor

(2) WAN poorten (GbE RJ45 en 10G SFP+) met failover support

(2) LAN poorten (GbE RJ45 en 10G SFP+)

Enterprise-class DPI, IPS/IDS, en gelaagde firewall configuratie

Power redundantie bij aansluiting op de UniFi SmartPower RPS (apart verkrijgbaar)

SmartPower outlet (125VAC/2A) voor een extern modem

1U-formaat, in een rack te monteren apparaat

Beheerd met de UniFi Network applicatie: Versie 5.14.11 en hoger.

Mechanical

Dimensions 442.4 x 43.7 x 285.6 mm

Weight 3.42 kg

Enclosure materials Front panel: aluminum CNC

Top cover/base: SGCC steel

Hardware

Processor Quad-core ARM Cortex-A57 at 1.7 GHz

Memory information 2 GB DDR4

Management interface Ethernet

Networking interface

LAN:

WAN:

(1) 1 GbE RJ45 port

(1) 10G SFP+ port

(1) 1 GbE RJ45 port

(1) 10G SFP+ port

LCM display (1) 1.3" touchscreen, Bootup animation: bootup in progress, Firmware upgrade icon: firmware upgrading

Button Factory reset

Power method (1) Universal AC input, 200-240VAC, 1.7A max., 50/60 Hz

(1) RPS DC input, 11.5VDC, 2.87A

Power supply AC/DC, internal, 50W

Max. power consumption 30W

ESD/EMP protection Air: +/- 15 kV, contact: +/- 8 kV

Operating temperature -10 to 40 C

Operating humidity 5 - 95% noncondensing

Certifications CE, FCC, IC

LEDs

AC outlet/ RPS Blue

Ethernet Green/amber

SFP+ White/green

Inhoud Verpakking

UXG-PRO, Schroevenset, Beugels, Stroomkabel, UC-DAC-SFP+ patch kabel.