

VDB Computers B.V.

Vlakdissel 9
1648 HJ De Goorn
info@vdbcomputers.nl
0229-544704

UniFi Switch Pro Aggregation

Artikelnummer: USW-Pro-Aggregation



€1.065,00

Incl. 21% BTW

Certifications	CE, FCC, IC
Dimensions	442 x 325 x 44 mm
ESD/EMP Protection	Air: +/- 16kV, Contact: +/- 12kV
Enclosure Material	SGCC Steel
Forwarding Rate	565.44 Mpps
LCM Display	(1) 1.3" Touchscreen Bootup Animation: Bootup in Progress Firmware Upgrade Icon: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
LEDs	SFP28/SFP+: White, Link and Activity
Management Interface	Ethernet In-Band
Max. Power Consumption	100W
Modes	SMB Layer 3 10/25 G Fiber Switch
Network Interface	(28) 1/10 Gbps SFP+ Ethernet (4) 1/10/25 Gbps SFP28 Ethernet
Operating Humidity	10 - 90% Noncondensing
Operating Temperature	-5 to 40 C
Power Method	(1) Universal AC input, 100-240VAC, 2A Max, 50/60 Hz (1) USP-RPS DC input, 11.5VDC, 8.7A
Switching Capacity	760 Gbps

Total Non-Blocking Throughput	380 Gbps
Weight Without Mount: With Mount	4.6 kg 4.7 kg

De UniFi Switch Pro Aggregation is een volledig beheerde Layer 3-switch met (4) 25G SFP28-poorten en (28) 10G SFP+-poorten.

De UniFi Switch Pro Agg...

De UniFi Switch Pro Aggregation is een volledig beheerde Layer 3-switch met (4) 25G SFP28-poorten en (28) 10G SFP+-poorten.

De UniFi Switch Pro Aggregation maakt gebruik van links met hoge bandbreedte om linkaggregatie te creëren die de switchcapaciteit verbetert.

De UniFi Switch Pro Aggregation wordt beheerd met de UniFi Network-applicatie (web en mobiel), zodat u eenvoudig uw bedrijfsnetwerken kunt bouwen, schalen en bewaken

(28) 10 Gbps SFP+ poorten

(4) 25 Gbps SFP28 poorten

760 Gbps switchvermogen

(1) 1.3" touchscreen met AR-switchbeheer

(1) Backup 12V DC ingangsconnector, SmartPower RPS